



RS660

aprilia®



RS660

**BACKLIT
SWITCHCUBES**

**α-PRC* SYSTEM, 5 RIDING MODES:
AEM, AEB, ATC, ALC, AWC, ACC**

**BONDED 5" TFT
DASHBOARD**

ALUMINUM FRAME

**KAYABA MONOSHOCK,
REBOUND AND PRELOAD
ADJUSTABLE**

CORNERING ABS

**UP&DOWN
QUICKSHIFTER**

**KAYABA Ø 41 MM
USD FORK, REBOUND
AND PRELOAD
ADJUSTABLE**

**BREMBO
RADIAL CALIPERS**

**E5+ PARALLEL TWIN
659 CC, 105 HP**

WET WEIGHT 183 KG

* **Aprilia Performance Ride Control** Engine Maps (AEM), Engine Brake (AEB), Traction Control (ATC), Wheelie Control (AWC), Aprilia Launch Control (ALC), Cruise Control (ACC)

RS660

Engine	
Type	Parallel twin, 4 valves per cylinder, liquid-cooled with Ride-By-Wire
Displacement	659 cc
Bore x Stroke	81 x 63.93 mm
Max Power	105 Hp (77.2 kW) @ 10,400 rpm
Max Torque	70 Nm @ 8,400 rpm
Clutch	Multi plate wet clutch with slipper system
Gearbox	6 speed
Chassis	
Frame	Twin spar aluminum frame
Front Suspension	Kayaba Ø 41 mm USD Fork, rebound and preload adjustable, 120 mm travel
Rear Suspension	Kayaba monoshock, rebound and preload adjustable, 52 mm travel
Front Brake	Double Ø 320 mm floating disc. Brembo radial calipers
Rear Brake	Ø 220 mm disc. Brembo caliper
Front Wheel	Cast wheel 17" x 3.5"
Rear Wheel	Cast wheel 17" x 5.5"
Dimensions & Weights	
Seat Height	820 mm
Fuel Tank Capacity	15 L
Wet Weight*	183 Kg
Emissions Compliance	Euro 5+
Std. Features	
Standard Features	Full LED headlight and indicators with light signature. Bonded 5" TFT dashboard. Backlit switchcubes. a-PRC system with 6-axis inertial platform: Engine Maps (AEM), Engine Brake (AEB), Cornering (3 maps and Rear Wheel Lift-up Mitigation), Traction Control (ATC), Wheelie Control (AWC), Aprilia Launch Control (ALC) ,5 Riding Modes. Cruise Control (ACC). Aprilia Quick Shift (AQS). Metal Braided Brake Hoses

* According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume

COLOUR RANGE 2025



BLUE MARLIN



VENOM YELLOW



The company reserves the right to make technical and aesthetic changes at any time. Full information on models and accessories is available at www.aprilia.co.id. Ride carefully, always wearing a helmet and suitable gear. Always comply with the rules of the road and respect the environment. Read the operating and maintenance manual carefully. Always ask for original and approved spare parts in accordance with current legislation. Visit an Official Aprilia Dealership or Authorised Retailer for a secure purchase and guaranteed service support.

PT Piaggio Indonesia customer service: (021) 1500 585, customer.service@id.piaggio.com

COMPANY WITH ENVIRONMENTAL SYSTEM CERTIFIED BY DNV
= ISO 14001 =

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV
= ISO 9001 =

COMPANY WITH SAFETY SYSTEM CERTIFIED BY DNV
= OHSAS 18001 =

Aprilia is a registered trademark of Piaggio & C. S.p.A.

For more information
visit aprilia.co.id



THE STUNNERS | 2024

| ACID GOLD

| TRIBUTE

RS660

Engine	Aprilia forward-facing parallel twin, four stroke, liquid-cooled with radiator and water-oil heat exchanger, DOHC with silent chain on the right side, four valves per cylinder
Engine capacity	659 cc
Max power	73.5 Kw (100 HP) at 10,500 rpm
Max torque	67.0 Nm at 8,500 rpm
Chassis	Aluminium dual beam chassis with removable seat-supporting subframe
Fuel system	Airbox with front air vent. Two 48 mm throttle bodies. Ride-by-wire management
Transmission	Six gears with Aprilia Quick Shift (AQS) up and down system
Front suspension	Kayaba Ø 41 mm upside down fork with top out spring, Aluminium pins to fasten radial callipers adjustment 120 mm wheel travel
Rear suspension	Asymmetrical aluminium swingarm. Single shock and top out spring with rebound and spring pre-load adjustment 52 mm wheel travel
Front brake	320 mm diameter double disc. Brembo radial callipers with 4 horizontally opposed 32 mm pistons. Radia pump and metal braided brake hose
Rear brake	220 mm diameter disc. Brembo calliper with two 34 mm separate pistons. Pump with integrated tank an metal braided hose
ABS system	Multimap Cornering ABS
Front wheel	3.5"x17" aluminium alloy wheel-Tubeless radial tyre, 120/70 ZR 17"
Rear wheel	5.5"x17" aluminium alloy wheel-Tubeless radial tyre, 180/55 ZR 17" (alternatively 180/60 ZR17)
Seat height	820 mm
Fuel tank capacity	15 L (1 L reserve)
Kerb weight	183 kg (In compliance with VO (EU) 168/2013 standards, with all operating liquids, with standard equipm and fuel tank filled to at least 90% useful capacity)
Electronic management	6-axis IMU, a-PRC suite that includes ATC (traction control), AWC (wheelie control), AEB (engine brake) AEM (engine mapping), ACC (cruise control) 5 riding models (Road and Track, E pre-set and 2 customisable)
Compliance	Euro 5

*Accessories and merchandise are sold separately and subject to availability.

COLOUR RANGE 2024



ACID GOLD



TRIBUTE



The company reserves the right to make technical and aesthetic changes at any time. Full information on models and accessories is available at www.aprilia.co.id. Ride carefully, always wearing a helmet and suitable gear. Always comply with the rules of the road and respect the environment. Read the operating and maintenance manual carefully. Always ask for original and approved spare parts in accordance with current legislation. Visit an Official Aprilia Dealership or Authorised Retailer for a secure purchase and guaranteed service support.

PT Piaggio Indonesia customer service: (021) 1500 585, customer.service@id.piaggio.com

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV
= ISO 14001 =

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001 =

COMPANY WITH
SAFETY SYSTEM
CERTIFIED BY DNV
= OHSAS 18001 =

**For more information
visit aprilia.co.id**

Aprilia is a registered trademark of Piaggio & C. S.p.A.



aprilia.co.id