



aprilia



APRILIA SR-GT SPORT 200 & APRILIA SR-GT REPLICA

Engine	Single-cylinder 4-stroke i-get with Start&Stop system
Engine capacity	174 сс
Bore x stroke	61.5 mm x 58.7 mm
Max. power	13 kW at 8,500 rpm
Max. Torque	16.5 Nm at 7,000 rpm
Valve timing system	Single overhead camshaft, 4 valves
Cooling	Liquid
Fuel system	Electronic injection
Lubrication	Wet sump
Starter	Electric
Transmission	Continuously variable transmission (CVT)
Clutch	Automatic centrifugal dry clutch
Chassis	Double cradle, in high-resistance steel tubing
Front suspension	Hydraulic telescopic fork ø 33 mm (120 mm travel)
Rear suspension	Double hydraulic shock absorber with adjustable preload (102 mm travel)
Front brake	Hydraulic with wave disc, Ø 260 mm - ABS
Rear brake	Hydraulic with wave disc, 0 220 mm
Front tyre	Tubeless 110/80 - 14"
Rear tyre	Tubeless 130/70 - 13"
Length	1,920 mm
Width	765 mm
Seat height	799 mm
Wheelbase	1,350 mm
Fuel tank capacity	91
Emissions compliance	EURO 3

The company reserves the right to make technical and aesthetic changes at any time. Full information on models and accessories is available at www.aprilia.co.id. Ride carefully, always wearing a helmet and suitable gear. Always comply with the rules of the road and respect the environment. Read the operating and maintenance manual carefully. Always ask for original and approved spare parts in accordance with current legislation. Visit an Official Aprilia Dealership or Authorised Retailer for a secure purchase and guaranteed service support.

PT Piaggio Indonesia customer service: (021) 1500 585, customer.service@id.piaggio.com

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV
= ISO 14001=

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001 =

COMPANY WITH SAFETY SYSTEM CERTIFIED BY DNV = OHSAS 18001 =







II GP REPLICA





II SAVANA GREY MATTE



II SPACE WHITE MATTE



II STREET GOLD MATTE